



**ELITE EBP
220TD**
Barcode
Printer



THERMAL TRANSFER/ DIRECT THERMAL

Barcode printer

- Support thermal transfer and direct thermal printing
- Max print speed up to 127mm/s
- 8MB flash memory, 8MB SDRAM
- Ribbon core inner diameter: 0.5"
- Bartender special edition
- USB + BLUETOOTH

PRODUCT PARAMETERS

Resolution	203 DPI
Print method	Thermal Transfer /Direct Thermal
Print speed	127 mm (5")/s Max.
Max.print width	108 mm(4.25")
Max.print length	1778 mm(70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4-118mm (1.0"-4.6")
Media thickness	0.06~0.254 mm
Media core diameter	25.4 ~ 50.8 mm (1" ~ 2")
Ribbon length	Max.90m
Ribbon width	25.4mm-110mm (1"-4.3")
Label length	10 mm ~1778 mm
Label roll capacity	127 mm (5") OD(outer diameter)

PRODUCT PARAMETERS

Ribbon core inner diameter	12.7 mm(0.5")
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4Gb
Interface	USB(Optional:WIFI/Bluetooth/TF card)
Sensors	① Gap sensor Black ② Cover opening sensor ③ Bmark sensor ④ Ribbon sensor
Internal fonts	8 alpha-numeric bitmap fonts,Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and
2D barcode	PDF-417, Maxicode, DataMatrix, QR code
Rotation	0°, 90°, 180°, 270°
Emulaion	TSPL, EPL, ZPL, DPL
Dimension	246 × 199 × 168mm(D×W×H)
Weight	1.62kg

PRODUCT PARAMETERS

Print head life	30 km
Driver	Windows/Linux/Mac
SDK	Windows/Android/iOS
Input	AC 100-240V
Output	DC 24V, 2.5A
Factory Options	① Bluetooth module ② WiFi module ③ Real clock ④ Cutter
Dealer Options	① External paper roll holder ② Paper roll spindle ③ Extension board for external paper roll holder ④ Shipment waybill box
Operation	5 ~ 40° (41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60° (-40~140°F), Humidity: 10 ~ 90% non-condensing



www.elite-eu.com



info@elite-eu.com